



+1 (920) 234 5113

+852 2635 2285

+52 (55) 55 74 20 76

+86 147 154 84260

email: [info@gseint.com](mailto:info@gseint.com)

web: [www.gseint.com](http://www.gseint.com)



## Twin Headed Rocking Piston

ZW400 3rd Gen

Open Flow **4.94cfm (140lpm)**

Max. Pressure (INT.) **44psi (3bar)**


Max. Vacuum **26.6"Hg (-900mbar)**

- Permanently lubricated bearings
- Oil-less, non-lubricated cup and cylinder
- Long-life cup design
- Thin wall cylinder for good heat transfer
- Stainless steel valves
- Capacitor as standard
- Field service ability
- Recoverable thermally protected motor
- Other voltage and configuration available upon request

### Specifications

Model	ZW400A-90/2-(3)	ZW400D2-115/1.4
Rated Voltage	220V/50Hz	115V/60Hz
Rated Input Power	510W	600W
Input Current	3.8A	5.45A
Air Flow at rated Pressure	90LPM	115LPM
Max. Continuous Pressure	2bar	2bar
Max. Intermit Pressure	3bar	3bar
Noise Level	61dBA	61dBA
Restart Pressure	0Kpa	0Kpa
Ambinet Temperature	5-40°C	5-40°C
Insulation Class	B	B
Insulation Resistance	> 500M ohm	> 500M ohm
Thermal Protect	135±5°C	135±5°C
Capacitor Included	12.5µF	30µF
Weight	7.5kg	7.5kg

### Performance Chart



The information presented in this material is based on technical data and test results of nominal units. Its is believed to be accurate and reliable and is offered as an aid to help in the selection of GSE products. It is the responsibility of the user to determine the suitability of the product for their intended use and the user assumes all risk and liability whatsoever in connection therewith. GSE does not warrant, guarantee or assume any obligation or liability in connection with this information.

### Technical Drawings

