



+1 (920) 234 5113

+852 2635 2285

+52(55)55 74 20 76

+44 7716 825015

email: [info@gseint.com](mailto:info@gseint.com)

web: [www.gseint.com](http://www.gseint.com)



## Single Headed Rocking Piston

ZWS370


Open Flow **40lpm (1.41cfm)**  
 Max. Pressure **7bar (102psi) INT.**  
 Max. Vacuum **-880mbar (26"Hg)**

- Permanently lubricated bearings
- Oil-less, non-lubricated cup and cylinder
- Long-life cup design
- Thin wall cylinder for good heat transfer
- Stainless steel valves
- Capacitor as standard
- Field service ability
- Recoverable thermally protected motor

### Specifications

Model	ZWS370F-23/3.5M	ZWS370D2-23/3.5M
Rated Voltage	230V/50Hz	115V/60Hz
Rated Input Power	300W (0.40HP)	250W (0.34HP)
Input Current	1.7A@3.5bar	2.5A@4bar
Air Flow at rated Pressure	22LPM@3.5bar 0.78CFM@51psi	21LPM@4bar 0.74CFM@58psi
Max. Continuous Pressure	3.5bar (51psi)	4bar (58psi)
Max. Intermit Pressure	7bar (102psi)	7bar (102psi)
Noise Level	57dBA	60dBA
Restart Pressure	0Kpa (0psi)	0Kpa (0psi)
Ambinet Temperature	5-40°C (41-104°F)	5-40°C (41-104°F)
Insulation Class	B	B
Insulation Resistance	> 500M ohm	> 500M ohm
Thermal Protect	135±5°C (275±9°F)	135±5°C (275±9°F)
Capacitor Included	10µF	30µF
Weight	5kg (11.0lbs)	5kg (11.0lbs)

### Performance Chart



The information presented in this material is based on technical data and test results of nominal units. Its is believed to be accurate and reliable and is offered as an aid to help in the selection of GSE products. It is the responsibility of the user to determine the suitability of the product for their intended use and the user assumes all risk and liability whatsoever in connection therewith. GSE does not warrant, guarantee or assume any obligation or liability in connection with this information.

### Technical Drawings

